



SILENCER  
CENTRAL

# BANISH Backcountry

**BANISH® Suppressors are the original multi-caliber suppressor and have been setting the standard for modular suppressor design since 2009. As “the one that fits any gun,” BANISH Suppressors are more than just a multi-caliber suppressor, they are also packed full of innovative design features that BANISH both sound and recoil.**

BANISH® Suppressors, made by Silencer Central, are the original multi-caliber suppressor and have been setting the standard for modular suppressor design since 2009. As “the one that fits any gun,” BANISH Suppressors are more than just a multi-caliber suppressor, they are also packed full of innovative design features that BANISH both sound and recoil.

BANISH Suppressors has always had one overriding goal in mind - to make the most user-friendly suppressor on the market. And what is more user-friendly than being multi-caliber? At Silencer Central, we are proud of what we’ve accomplished, and we want to share with you what makes a BANISH Suppressor “stand out from the crowd”.

Our products are all manufactured with high quality, lightweight titanium alloy. BANISH Suppressors are light-weight and tough enough for a lifetime of service. The baffles handle the gas in such a way that the suppressor significantly reduces recoil as well as sound.

## **WARNING**

To provide for your safety and the effective use of this silencer, it is important that the owner and any user of the silencer read this entire manual and strictly follow the warnings and instructions within. This silencer should be used only by those who are well-versed in the safe operation of firearms.

Failure to follow installation and maintenance instructions in this manual may result in serious personal injury and damage to the firearm.

Suppressed firearms make less noise than unsuppressed firearms and it is easy to forget that they are still capable of causing bodily injury and property damage. Remember, a suppressed firearm should be treated with the same safety and caution as an unsuppressed firearm. Before installing the silencer, be sure that the firearm is unloaded and the action is opened and visibly clear of any ammunition. If you are at all unsure as to the proper procedures to ensure that your firearm is unloaded, please consult your firearm user's manual/instructions and/or contact a properly licensed dealer or the manufacturer of your firearm.

Firearm silencers are user-attached firearm muzzle devices, and as such are subject to improper attachment issues unless the procedures outlined in this manual are followed precisely.

Check the fit between your barrel and silencer before firing! The thread mount must be fully shouldered on the barrel. For direct thread silencers, there should be no visible gap between the barrel shoulder and the face of the silencer thread mount (crush washer from muzzle brake must be removed).

For quick detach suppressors, the muzzle brake must be seated to the shoulder of the firearm and timed properly using the shim kits provided.

If there is any gap DO NOT fire the host with the silencer attached. Poor accuracy and product damage may result if the silencer is not seated against thread shoulder.

Silencers must be free of obstructions such as mud, dirt, etc. DO NOT attempt to shoot through an obstructed silencer.

The silencer is designed to suppress the initial muzzle blast and subsequent projectile de-corking pressure. The silencer doesn't contact or otherwise interact with the bullet, allowing the projectile to travel at its default speed.

A sonic crack may be produced by the projectile as it breaks the sound barrier. This is solely a function of the projectile breaking the sound barrier and is not related to product performance.

To ensure your silencer remains secure while firing, it is of the utmost importance that you frequently verify the silencer is securely tightened onto the barrel. We recommend checking the security of the attachment after 5 discharges of the firearm and every 30 discharges thereafter.

Before removing the silencer from the host firearm, be sure that the firearm is unloaded, and the action is opened so that it is visibly clear of any ammunition. When removing the silencer, use extreme caution as it may be hot to the touch after firing. Use a Devour™ suppressor cover (sold separately) or gloves to avoid burns or other injuries.

Once the silencer is removed from the host firearm, BANISH recommends using a thread protector or other muzzle device to protect the muzzle threads and crown during storage or transport.

## CALIBERS & RESTRICTIONS

**.300 Remington Ultra Magnum rated.**

Rifle 300 RUM, 300 Win Mag, .308 Win  
down to .223/5.56 Remington and 6.5 Creedmoor.

### DIAMETER

1.6"

### WEIGHT

7.8 oz (w/o Mount)  
9.0 oz (w/ DT Mount)

### LENGTH

5.5" (w/o Mount)  
5.7" (w/DT Mount)

### BAFFLES

6 - Qty=5 Baffles and Qty=1 Accuracy Baffle

### MATERIALS

100% titanium

\*\*Direct Thread Mounting - 1/2 x 28 TPI, 5/8 x 24 TPI, 5/8 x 32 TPI, 11/16 x 24 TPI, 3/4 x 24 TPI

\*\*Muzzle Brake - 1/2 x 28 TPI, 5/8 x 24 TPI, 11/16 x 24 TPI, 3/4 x 24 TPI

\*\*See Website, or speak to a sales associate, about alternate thread pitches for both direct thread and muzzle brakes not listed.



The BANISH Backcountry is designed specifically for hunting. It gives you accuracy without the extra weight when its time to take the perfect shot. The short length allows you to move comfortably and confidently in any terrain.

All Banish® suppressors have been designed for unmatched sound suppression. Testing shows that the Banish Backcountry has an average, at ear, meter reading of 135 dB for .308 WIN, 137 dB for 300 Win Mag, and 138 dB for 300 RUM, all configured with 20" barrels.

Like all Banish suppressors, the Banish Backcountry is made from a strong, Titanium alloy for unmatched durability, at an extremely light weight.

At under 6 inches, you'll hardly notice the suppressor on the end of your rifle.

Perfect for hunting, but also a plus for at the range, the Banish Backcountry will significantly reduce the report and recoil of large-caliber rifles.



## INSTALLATION OF SUPPRESSOR

Prior to mounting the suppressor to the firearm, you must first thread and tighten the mount (shipped with the suppressor) into the suppressor. Carefully thread the mount into the suppressor and tighten to 50-60 in-lbs.

Muzzle brakes will require a secondary attachment, sold separately, to be able to attached to the BANISH Backcountry.

### INSTALLATION OF SUPPRESSOR - DIRECT THREAD

Always ensure the firearm is unloaded when attaching or removing suppressor. After confirming that your firearm is unloaded, place the threaded end of the BANISH Backcountry in line with the threads of the barrel.

Ensure the threads on the barrel and suppressor are clean and undamaged, screw the suppressor onto the barrel threads until the suppressor firmly seats against shoulder.

Take special care to avoid cross-threading as damage to the suppressor and barrel threads will result, as well as misalignment of the suppressor with the bore of the firearm.

This may result in a potential baffle strike that could cause serious personal injury and damage to both the firearm and suppressor. Since direct thread mounted suppressors can loosen or unscrew during firing, it is extremely important that the operator frequently checks that the silencer remains securely threaded to the barrel.

Please note, the suppressor will be very hot during and after firing. Wait until the suppressor cools or use a Devour™ suppressor cover to retighten.

Hand tighten suppressor only. Ready for use.



## INSTALLATION OF MUZZLE BRAKE AND SUPPRESSOR

Always ensure the firearm is unloaded when attaching or removing a muzzle brake or a suppressor. After confirming that your firearm is unloaded, remove any preceding muzzle device and crush washer.

Watch our online tutorial on how to install a muzzle brake and shim kit at [www.YouTube.com/SilencerCentral](http://www.YouTube.com/SilencerCentral)

Items included will be the actual muzzle brake and necessary shim kit. You will need to use Red Loctite/Rocksett (not included).

1. Make sure to clean the threads of your barrel prior to installation of the muzzle brake.
2. Attach the new muzzle brake onto the barrel all the way by hand without using shims until it shoulders tight to the barrel.
3. Unscrew the muzzle brake so that the center point (engraved BANISH) is perpendicular to the plane of the barrel in the 12 o'clock position. The 12 o'clock position will be the final orientation of the muzzle brake with BANISH logo facing directly upward (see figure 1). Note: when you back the muzzle brake off of the shoulder it should be less than a full 360-degree rotation of the muzzle brake.
4. Once the brake is placed at the 12 o'clock position, unscrew one additional quarter turn to the 9 o'clock position. This will allow tightening the muzzle brake into the correct position.
5. The space between the brake and the shoulder of the barrel located at the rear of the threads will be where the shims will sit. Select the shims with varying thickness that will fit snugly in this space. This will be different on every firearm and may require some trial and error. Use as few shims as possible to fill the void is the best practice. Start with the thickest shim and find the best combination that allows for the tightest fit within the space between the muzzle brake and barrel shoulder. Save excess shims for later use. (See figure 2)
6. Once you have found the combination resulting in the tightest fit, remove the brake completely from the barrel and place that combination of shims over the threads of the barrel against the shoulder. Then screw the brake onto the threads of the barrel by hand. If this process has been completed correctly the brake should return to the BANISH logo resting at the 9 o'clock position.
7. Using a crescent wrench or  $\frac{3}{4}$ " wrench tighten the muzzle brake  $\frac{1}{4}$  turn to allow for the muzzle brake to sit at the 12 o'clock position.
8. Once the practice timing is perfect in the 12 o'clock position, remove the muzzle brake completely from the barrel and apply Red Loctite or Rocksett. Once applied, repeat steps 6&7 to set the muzzle brake in place.
9. You are now ready to install your BANISH 46 Suppressor. Line up your BANISH 46 suppressor with the muzzle brake and screw it on hand tight.

## CLEANING

It is recommended that the suppressor be cleaned every 50 - 100 rounds fired. The use of solid lead or plated lead bullets is not recommended.

To clean make sure the firearm is unloaded and remove from host firearm.

The BANISH Backcountry is not user-serviceable, meaning it is fully welded and the baffles cannot be removed. The only part that can be removed for cleaning is the mount interface.

Place the silencer into a sonic wash for one to two cycles, or soak in a cleaning solution for one to two days. Any firearm solvent or sonic wash firearm cleaning solution will work. Ensure not to use solutions that will strip the Cerakote coating from the silencer. Once soaked, take a brass brush, and clean the blast chamber and accuracy baffle. Ensure to remove the mount and thoroughly clean the threads of any debris or buildup. This should be done for both the silencer threads, as well as the mount's internal, and external, threads.

Once clean, allow the suppressor to dry. Re-install the mount and you are ready to shoot again. Shoot 10-15 rounds through the suppressor. The high pressure will shoot out any loose debris and buildup that was loosened during cleaning.



## **GUARANTEE, WARRANTY, AND CANCELLATION POLICY**

### **YOUR SILENCER DONE RIGHT, GUARANTEED**

We make getting a silencer simple—and we commit to doing it right, every time.

We guide you through every step, with expert advice from real people. We commit to responding to your questions and concerns within 2 business days.

We leave no detail overlooked. We commit to completing your paperwork right, the first time. If you provide accurate information and Silencer Central makes an error on your application that results in a disapproval from the ATF, we will refund the cost of your tax stamp and work quickly to get you resubmitted.

We engineer our BANISH® Suppressors to the highest levels of quality, reliability, and performance. BANISH Suppressors ship with a warranty against defects in manufacturing, but we also guarantee satisfaction and performance. If your BANISH Suppressor does not significantly reduce the report and recoil of your firearm, we'll buy it back. Learn more.

We ship with care. Our silencers are carefully packaged surrounded in durable foam and encased in a hard-sided box to prevent any damage from occurring during transit. When shipping your barrel(s) for gunsmithing services, we commit to repairing or replacing any firearm damaged in transit, so long as all shipping specifications have been met. When it comes to delivery, if your silencer is lost or stolen, we will cover the cost and work quickly to get you resubmitted.

### **NFA ITEM CANCELLATION POLICY**

If for any reason you change your mind after purchasing and wish to cancel your order, you will receive your full cost of purchase back, including your tax stamp, less a 25 percent processing fee which will be issued in the form of a credit to be applied to a future purchase, which credit must be redeemed within one calendar year of cancellation. Cancellation must be within 30 days of purchase and before any ATF paperwork has been submitted for the item. Unfortunately, once application forms have been submitted to the ATF, we are unable to cancel your order. Purchase of all sale items is final and no cancellation or refund will be issued.

### **RETURN POLICY FOR NON-NFA ITEMS**

Silencer Central will accept returns for all accessory items within 30 days of your purchase, provided the accessories are unused and received in the original packaging. Returns are honored in the form of credit toward a future purchase with Silencer Central or replacement product for defective or damaged items. Credits must be redeemed within one year of the return or are subject to forfeiture. Note: customers are responsible for any incurred shipping fees on returns.

## **GUARANTEE, WARRANTY, AND CANCELLATION POLICY**

### **BANISH SUPPRESSOR GUARANTEE**

If your BANISH® Suppressor doesn't significantly reduce the report of your firearm, as well as recoil, we'll buy it back within 30 days. If performance concerns are noted, you can send your BANISH Suppressor back to be reviewed on a case-by-case basis. We will field test your BANISH Suppressor and provide documentation of actual noise reduction and/or recoil results to satisfy our commitment to performance satisfaction. Additionally, we guarantee the quality and craftsmanship of your BANISH Suppressor. After you are approved and you receive your BANISH Suppressor, you may return your BANISH Suppressor to Silencer Central for a full refund in the form of a Silencer Central gift certificate (tax stamp not included). All returns must be within 30 days of confirmed delivery.

The following terms and conditions apply:

- This offer only applies subsequent to the Form 4 being approved by the ATF. BANISH® Suppressor orders cannot be canceled or refunded while the Form 4 is pending.
- Tax stamp payments will not be refunded.
- The value of any promotional items earned as part of the original purchase (e.g., free accessories, etc.) will be deducted from the refunded amount.
- To process a return, you must first contact Silencer Central to receive a return authorization number and begin the Form 4 submission process to transfer back. At that time, you will receive instructions on how and when to return the BANISH® Suppressor. Following these instructions is required.
- ATF approval is required before the BANISH Suppressor can be returned to Silencer Central. Silencer Central is not responsible for any delays caused by the ATF.
- The refund will be given once Silencer Central receives said BANISH Suppressor back into our NFA inventory.
- To receive a full refund, all respective accessories, cases, manuals, and original packaging must accompany your returned BANISH Suppressor. Your original approved Form 4 is also required
- All refunds will be in the form of a Silencer Central Gift Certificate, which is not redeemable for cash.
- Please Note: Silencer Central reserves the right to modify this guarantee at any time without notice. Moreover, Silencer Central reserves the right to refuse specific cases deemed fraudulent. Thank you for your business.

### **WARRANTY REPAIR**

For warranty claims on BANISH Suppressors, please print and fill out the warranty repair request form.

Please contact our Customer Service Department at 888-781-8778 for further details and requirements or visit [silencercentral.com](http://silencercentral.com).