

SUPPRESSOR

FACTS

SERVING SIZE:

1 CAN (12.8 OZ)

CAL. PER SERVING: 5.56

% DAILY INTAKE

VITAMIN 2A 100%

VITAMIN USA 1776%

VITAMIN LOUD 0%

Cartridge 5.56 Nato

Overall Length 5.59"

Length w/ Adapter 6.5"

Diameter 1.5625"

Weight w/ Adapter 12.8oz

Decibel rating 134 dB

Min. Barrel Length 10"

Mount

1.375x24 - HUB Interface

Flash Hider or Muzzle Brake

Construction

Primary Metal

17-4 Stainless Steel
(Heat-Treated)

Blast Baffle

718 Inconel
(Heat-Treated)

Finish

High Temperature
Black Cerakote



TURBO T3 CONTAINS:

- New technology from YHM® Engineers
- A design improvement aimed primarily to reduce *blow back*



VISIT: YHM.NET/INSTALLATION-INSTRUCTIONS/
FOR MORE DETAILED INSTRUCTIONS

YANKEE HILL MACHINE CO.

THE

TURBO T3

YHM

The wait is over..
Meet your new

TURBO T3


The Phantom® Q.D. Adapter is a proprietary mounting system and requires a complementary muzzle device (included).

INSTALLATION AND USE

phantom® q.d. adapter:



(1) Thread the Phantom® Q.D. Adapter (1A) into the Turbo® T3 suppressor body (2A) by hand, taking care not to cross-thread



(2) Hold the Turbo® T3 body (2A) with a firm grip. Using the supplied wrench (3A) to grasp notches in the base of the Adapter (1A). Tighten the adapter in a clockwise direction. Torque to approximately 35 ft-lbs



MUZZLE DEVICE:

(1) Remove your existing muzzle device and crush washer (if any).

(2) Inspect threads for damage or wear.

(3) Install the YHM® Muzzle Device (1B) by threading it onto the barrel (2B).

If you have received a Q.D. Muzzle Brake Mount, use the provided shim kit to ensure proper Muzzle Device Alignment



(4) Tighten onto your barrel using a 3/4" open end wrench.

For proper alignment, it is essential that the muzzle device seats against a 90° barrel shoulder. The muzzle device should be torqued to 20-30 ft-lbs.

SUPPRESSOR:

(1) Install the Turbo® T3 Assembly (2C) by sliding the back end over the YHM® Phantom® Q.D. mount (1C) until it stops. Then Turn the suppressor (2C) clockwise to hand tighten



(2) You will hear the locking mechanism click as the suppressor is tightened. Continue to tighten until the ratcheting stops to ensure a correct seal.

(3) To remove the suppressor, simply unscrew from the Q.D. mount.

COMPATIBLE MUZZLE DEVICES

Phantom Q.D. Adapter
The sRx System

4302 Series
5M2-QD

4302-MB Series
3102-1MB Series

Kurz Adapter
Direct Thread Mount